



Cat[®] Material Handling Buckets

950–980 WHEEL LOADERS

Material Handling Buckets are available for pin-on interface interface and for use with the Fusion™ Coupler System. GET options available. Contact your Cat[®] dealer for more information.

All buckets are Performance Series unless shaded.

Fusion™

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950H	2,894	(114)	3.80	(5.00)	1,701	(3,750)
962H	2,894	(114)	3.40	(4.50)	1,373	(3,027)
	2,894	(114)	3.80	(5.00)	1,453	(3,203)
950K	2,894	(114)	2.70	(3.50)	1,373	(3,027)
962K	2,894	(114)	2.90	(3.75)	1,425	(3,142)
	2,894	(114)	3.10	(4.00)	1,474	(3,250)
	2,894	(114)	3.30	(4.25)	1,518	(3,347)
	2,894	(114)	3.40	(4.50)	1,556	(3,430)
	2,894	(114)	3.60	(4.75)	1,596	(3,519)
	2,894	(114)	3.80	(5.00)	1,650	(3,638)
IT62G / IT62H	2,894	(114)	3.40	(4.50)	1,156	(2,549)
	2,894	(114)	3.80	(5.00)	1,214	(2,677)
966H / 966K	3,201	(126)	4.00	(5.20)	2,068	(4,559)
	3,201	(126)	4.20	(5.50)	2,114	(4,660)
	3,201	(126)	4.40	(5.75)	2,383	(5,254)
	3,201	(126)	4.60	(6.00)	2,206	(4,863)
	3,201	(126)	4.80	(6.30)	2,254	(4,969)
972H/ 972K	3,201	(126)	5.20	(6.75)	2,274	(5,013)



Americas North



Cat Material Handling Buckets

Pin-on

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m ³	(yd ³)	kg	(lb)
950H	2,921	(115)	3.10	(4.00)	1,400	(3,087)
962H	2,921	(115)	3.30	(4.25)	1,445	(3,186)
	2,921	(115)	3.40	(4.50)	1,490	(3,285)
	2,921	(115)	3.80	(5.00)	1,558	(3,435)
	2,946	(116)	4.20	(5.50)	1,725	(3,800)
	2,946	(116)	4.40	(5.75)	1,907	(4,200)
	2,946	(116)	5.70	(7.50)	1,879	(4,140)
950K	2,894	(114)	2.70	(3.50)	1,495	(3,296)
962K	2,894	(114)	2.90	(3.75)	1,551	(3,419)
	2,894	(114)	3.10	(4.00)	1,601	(3,530)
	2,894	(114)	3.20	(4.25)	1,649	(3,635)
	2,894	(114)	3.40	(4.50)	1,689	(3,724)
	2,894	(114)	3.60	(4.75)	1,733	(3,821)
	2,894	(114)	3.80	(5.00)	1,787	(3,940)
IT62G / IT62H	2,927	(115)	3.10	(4.00)	1,242	(2,737)
	2,927	(115)	3.20	(4.25)	1,259	(2,775)
	2,927	(115)	3.40	(4.50)	1,293	(2,850)
966H / 966K	3,201	(126)	4.00	(5.25)	2,173	(4,791)
	3,201	(126)	4.20	(5.50)	2,217	(4,888)
	3,201	(126)	4.40	(5.75)	2,482	(5,472)
	3,201	(126)	4.60	(6.00)	2,304	(5,079)
	3,201	(126)	4.80	(6.25)	2,350	(5,181)
972H / 972K	3,193	(126)	4.60	(6.00)	2,269	(5,002)
	3,193	(126)	5.20	(6.75)	2,389	(5,267)
980H / 980K	3,405	(134)	5.70	(7.50)	2,882	(6,354)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

GEHQ0027 (02-14)

©2014 Caterpillar
All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

